

PedestalPro FH

FIXED HEAD ADJUSTABLE
PEDESTALS



Product Datasheet

The PedestalPro FH (fixed head) adjustable pedestal offers a high quality and economical option for supporting paving systems on completely level surfaces.

Its impressive 22 – 550mm height range makes it perfect for areas with problematic height restrictions, as well as areas where greater height build up is required. With a simple but very effective design, this pedestal makes for rapid and effortless paving installations.



KEY BENEFITS

- Robust product ensuring stability of paving area
- Perfect for very low height installations; adjusts down to 22mm
- Accommodates all types of calibrated paving - concrete, granite, porcelain, etc.

PAVING SUPPORT HEAD

Due to its low profile design, the support head allows this pedestal to go right down to 22mm height. The head utilises a clever connection which allows it to turn freely on top of the adjustable threaded section of the pedestal, meaning that the pedestal height can be adjusted once the paving is on top. Paving is spaced perfectly by the uniform spacer tabs.

HEIGHT EXTENSION COLLAR

The extension collar part adds 126mm of height by simply threading onto the base of the pedestal. This simple yet sturdy connection makes light work of supporting paving areas right up to 550mm. It is not necessary to determine how many of these extension collars are required; the correct quantity is supplied according to what pedestal size is chosen.

SUPPORT BASE

The broad base spreads the load on the surface below and ensures stability. The pedestals are normally loose laid onto roofing membranes which must not be penetrated, or can be mechanically fixed to concrete or other substrates.

ADJUSTABLE THREADED SECTION

The robust threaded section allows for incremental height adjustment within the given range. Effortless to adjust, simply turn the section by hand, even once the paving is in place.



PedestalPro FH

FIXED HEAD ADJUSTABLE
PEDESTALS



Product Datasheet

SIZE RANGE

The PedestalPro FH (fixed head) adjustable pedestal is the perfect solution where paving is to be supported on a totally flat area. Capable of supporting joists as low as 22mm off the surface, it will overcome the common problem of height restrictions, as well as quickly and simply elevating paving areas up to 550mm high.

TECHNICAL SPECIFICATIONS

Material	PP Polypropylene (recyclable), UV resistant
Biological/Chemical	Resistant to moulds, algae, alkali, bitumen
Height Range	22-35mm, 35-55mm, 55-95mm, 95-165mm, 165-235mm, 200-270mm, 260-340mm, 305-375mm, 365mm-445mm, 410-480mm, 470-550mm
Compression	1000kg
Base Diameter	200mm
Head Diameter	120mm
Spacer tab thicknesses	2mm / 4mm (standard) / 6mm
Working Temperature	-40°C – 120°C



OPTIONAL EXTRAS



Spacer Tab

Thickness Options: Standard: 4mm or Optional: 2mm/6mm



Base Rubber Shock Pad

Installed to enhance acoustic properties, or where membrane requires additional protection.



Head Rubber Shock Pad

Installed to enhance acoustic properties, and reduce movement with specific paving types, e.g porcelain.

PEDESTAL QUANTITY CALCULATIONS

For help calculating quantities of pedestals you require, or for any other guidance regarding your project, call Roof-Pro on 03335 771 500.