

## For sealing flat roof penetrations

### Applications

- For sealing flat roofing penetrations
- Particularly suitable for challenging or technical penetrations

Code	Internal dimension (mm)	To suit pipe diameters (mm)
PP-100	100	0-60
PP-150	150	0-110
PP-200	200	0-160
		Minimum 20mm of sealer between penetration and inside of ProPocket

Code	Description
PP-IC	Inside Corner
PP-OC	Outside Corner
PP-S-150	Straight 150mm
PP-S-250	Straight 250mm
PP-S-300	Straight 300mm

Code	Description	
Derbitech Seal Stick	310ml cartridge	Apply with skeleton gun to bond PocketPro to roof surface, seal the tongue and groove joint, and interface between pipe or penetration and existing roof surface
PocketPro liquid	Part A 3.86 kg/3420ml	Pour contents of Part B into part A. Thoroughly mix for 3-5 mins using PocketPro whisk with a drill
	Part B 1.28kg/1030ml	
PP-JUG	Jug for dispensing liquid	
PP-WHISK	Whisk for mechanically mixing two components	

Code	Contents
PPK-150	8 x PP-OC, 8 x PP-S-150
PPK-250	8 x PP-OC, 8 x PP-S-250
PPK-300	8 x PP-OC, 8 x PP-S-300

### Features

- Manufactured from polyurethane elastomer – absorbs stress and remains flexible
- Assembled on site and filled with fast setting solvent-free multi-use sealer – watertight within minutes
- When installed and filled with sealer, PocketPro becomes a long lasting homogenous seal
- Quick and easy installation, saving time and money
- Available in pre-fab, kit form and individual components



### PocketPro Tools (whisk)

