

ProDrain Plain Flange Rainwater Outlets

Applications

- Rainwater outlets for flat roof refurbishment and new build projects

Features

- High quality 400mm long spigot manufactured from stainless steel
- Flange is supplied plain stainless steel as standard, but can be primed if necessary
- Flange size - 330mm square
- O-ring seal supplied for refurbishment application - provides excellent seal whilst still allowing for movement

Code	Outlet Drain (mm)	To Suit Pipe Size (mm)	O-ring Seal Diameter (mm)	Flange	
				Type	Size (mm)
PRO-DRAIN-LL-40-PF	40	45-48	4.5	Plain	330 x 330
PRO-DRAIN-LL-50-PF	50	58-64	8	Plain	330 x 330
PRO-DRAIN-LL-62-PF	62	69-73	6	Plain	330 x 330
PRO-DRAIN-LL-70-PF	70	76-80	6 / UF-3*	Plain	330 x 330
PRO-DRAIN-LL-75-PF	75	82-95	8 / 12	Plain	330 x 330
PRO-DRAIN-LL-90-PF	90	100-108	10	Plain	330 x 330
PRO-DRAIN-LL-95-PF	95	103-109	8 / UK-4*	Plain	330 x 330
PRO-DRAIN-LL-110-PF	110	120-128	10	Plain	330 x 330
PRO-DRAIN-LL-125-PF	125	132-137	7	Plain	330 x 330
PRO-DRAIN-LL-145-PF	145	150-157	7 / UF-6*	Plain	330 x 330
PRO-DRAIN-LL-160-PF	160	170-178	10	Plain	330 x 330

*The PRO-DRAIN-LL-70, 95 and 145 can be used in conjunction with the UF seal - please enquire for details

