

# ProDrain rainwater outlets

## Applications

- Rainwater outlets for flat roof refurbishment and new build projects

## Features

- High quality 400mm long spigot manufactured from stainless steel
- Factory bonded flange to match specific membrane material being used (material must be specified at time of order)
- Membrane attached to the outlet allows for easy installation
- Flush finish - minimal risk of ponding
- O-ring seal supplied for refurbishment application - provides excellent seal whilst still allowing for movement

Code	Outlet Drain (mm)	To suit pipe size (mm) Where outlet is inserted into existing pipe in refurbishment situations	O-ring seal diameter (mm)	Membrane attachment	
				Type	Size (mm)
PRO-DRAIN-RW-40-SBS	40	45-50	5	Bituminous	500 x 500
PRO-DRAIN-RW-50-SBS	50	58-64	8	Bituminous	500 x 500
PRO-DRAIN-RW-62-SBS	62	70-76	8	Bituminous	500 x 500
PRO-DRAIN-RW-70-SBS	70	75-78	5/UF-3	Bituminous	500 x 500
PRO-DRAIN-RW-75-SBS	75	82-97	8/12	Bituminous	500 x 500
PRO-DRAIN-RW-90-SBS	90	98-108	10	Bituminous	500 x 500
PRO-DRAIN-RW-95-SBS	95	102-109	8/UF-4	Bituminous	500 x 500
PRO-DRAIN-RW-110-SBS	110	120-128	10	Bituminous	500 x 500
PRO-DRAIN-RW-125-SBS	125	135-143	10	Bituminous	500 x 500
PRO-DRAIN-RW-145-SBS	145	150-153	5/UF-6	Bituminous	500 x 500
PRO-DRAIN-RW-160-SBS	160	170-178	10	Bituminous	500 x 500

